

DragonScale Speed Weaving

Submitted by Olivea Peterson and Designed for Time. Rings used are 18 awg x 6mm ID and 18 awg x 3.5mm.

After taking some of her DragonScale apart Olivea realized that preclosing the small rings was possible by using the following technique.

Start by making two sections as pictured below. I like using a small piece of tape to hold the beginning of my weave stable. Rings as they are added will have a red dot on them.



Next set the section with the small rings on the ends on top of the other short section as shown below. Make sure the small rings on the top section are “in front of” the small rings on the bottom section.



Next take a large ring and go through the small ring from your bottom starter piece and before closing add another small ring. This ring should have 2 small rings on it once closed.



Take another large ring feeding it through the small ring just added and the one you went through with your previous large ring. It will also go through the other small ring from your bottom starter piece. Be sure to add another small ring before closing. Inspect closely and make sure that this large ring has gone through 4 small rings.



Take another large ring and run it through two small rings as show. One from the bottom of the weave and the other you just added with your last large ring.



Next take a large ring and run it thru two of the smaller rings as shown and add 2 small rings to it.



Take another large ring and run it thru as shown below and don't forget to add one small ring before closing.



This completes the cycle. Just repeat the steps above until you have the desired length you need.

All images and text remain the property of the author and are reproduced here with permission. You must obtain permission from the author to copy and/or distribute this tutorial.