## Vipera Berus Full Persian 6-1

**Revisions in Red** 

This weave was created by Loke and is acknowledged by M.A.I.L. The weave itself because of its structure is somewhat AR sensitive. I have used bronze for the Full Persian portion with an AR of ~6.5. The aluminum Vipera Berus portion has an AR of ~5.7. Bronze portion is 1,0mm x 6.5mm. Aluminum portion is 0,84mm x 4.80.

1. Start with either a short piece of Full Persian 6-1 weave or if so inclined make it to the length you want your finished piece to be. With the higher AR it should have a tendency to lay somewhat flat.



2. Once you have this completed you are ready for the Vipera Berus portion. Look closely at the orientation of the rings and capture the two rings as shown below.



3. Continue this capture to the end of the Full Persian weave.



4. The next section captures both the rings you just inserted and the bronze FP rings behind them.



5. Continue this portion to the end of the Full Persian weave.



6. Now lay your piece flat again and carefully observe the FP ring orientation. It should look like the picture below.





7. Now you're ready to capture the remaining ½ of the weave. Insert a ring through the two lower bronze rings as shown.

8. Continue this pattern to the end of your weave.



9. Final step is to again capture the Vipera Berus rings you just added and the bronze FP rings behind them.





10. Again continue this pattern to the end of the weave. Your resulting creation should look like this.